

Manufacturer, Supplier & Installer

DC Gravity & Controlled Descent and Non-Gravity Fail-Safe Tubular Motors



FEATURES

- Lifting capacity up to 200kg
- Gravity Fail-Safe feature available on models: DC55G, DC55G-25, DC80G, DC80G-19 & DC95G
- Suitable for use with Fire/Smoke Curtains, Fire Shutters and High Usage Doors
- Tested and approved by Exova, Warringtonfire

TECHNICAL INFORMATION

	DC55	DC55G	DC55G-25	DC80	DC80G	DC80G-19	DC95	DC95G
Voltage	24v	24v	24V	24v	24v	24v	24v	24v
Current	3.2a	3.2a	3.2a	8.5a	8.5a	8.5a	10.8a	10.8a
Running Time	30min	30min	30min	30min	30min	30min	30min	30min
Torque	30nm	15nm	25nm	80nm	80nm	30nm	120nm	100nm
RPM	18rpm	40rpm	25rpm	12rpm	12rpm	19rpm	10rpm	8rpm
Drop Weight	n/a	10kg	20kg	n/a	20kg	10kg	n/a	25kg
Lifting Capacity	50kg	20kg	40kg	100kg	80kg	40kg	200kg	90kg

	DC110	DC120	DC140	DC140Q	DC160
Voltage	24v	24v	24v	24v	24v
Current	10.8a	19.8a	18.5a	19.8a	14.6a
Running Time	30min	30min	30min	30min	30min
Torque	200nm	380nm	420nm	600nm	600nm
RPM	10rpm	8rpm	6.5rpm	140rpm	4.2rpm
Lifting Capacity	300kg	400kg	600kg	450kg	800kg