

Manufacturer, Supplier & Installer

DC Gravity & Controlled Descent and Non-Gravity Fail-Safe Tubular Motors



FEATURES

- Worldwide Patent
- Lifting capacity up to 600kg
- Gravity Fail-Safe feature available on models: DC55G, DC55G-25, DC80G, DC80G-18 & DC95G
- Suitable for use with Fire/Smoke Curtains, Fire Shutters and High Usage Doors
- Tested and approved by Exova, Warringtonfire

TECHNICAL INFORMATION

	DC55	DC55G	DC55G-25	DC80	DC80G	DC80G-18	DC95	DC95G
Voltage	24v	24v	24V	24v	24v	24v	24v	24v
Current	3.2a	3.2a	3.2a	8.5a	8.5a	8.5a	10.8a	10.8a
Running Time	30min	30min	30min	30min	30min	30min	30min	30min
Torque	12nm	6nm	10nm	50nm	50nm	25nm	100nm	40nm
RPM	18rpm	40rpm	25rpm	12rpm	12rpm	18rpm	12rpm	18rpm
Drop Weight	n/a	10kg	20kg	n/a	20kg	10kg	n/a	25kg
Lifting Capacity	40kg	20kg	35kg	100kg	100kg	50kg	200kg	80kg

	DC110	DC120	DC140	DC160
Voltage	24v	24v	24v	24v
Current	12.5a	14.5a	17.8a	21a
Running Time	30min	10min	10min	10min
Torque	150nm	240nm	350nm	480nm
RPM	12rpm	5rpm	5rpm	4.2rpm
Lifting Capacity	250kg	400kg	500kg	600kg

